



## Interface

介面 工業級乙太網 / 乙太網 TCP / IP / MODBUS TCP

## Mechanical data

尺寸 112 x 48 x 137 mm  
應用重量 550.00 g

## Material

外殼材質 鋁

## Remarks

在額定條件下，數值不得另行規定。

只能用於符合標準 ISO 15693 和 ISO 14443A 的數據載體。

This device is intended to be supplied by a UL-listed or CSA-certified power supply unit with "Class 2" or LPS power source.

The product is maintenance-free.

The device can be cleaned with a slightly damp cloth.


The devices must be installed permanently.

Check the function of the device and all associated components regularly by visual and functional testing. - In the event of malfunctions, take the device out of operation. - Secure the system against unauthorized use. - Check fastening and tighten if necessary. 1 Determine suitable mounting position. 2. Fasten the device with suitable mounting material.

有關 MTTF 及 B10d 的更深入資訊，請參見 MTTF / B10d 認證

此處所提供的 MTTF / B10d 值並非本公司承諾必定達成的特性及 / 或使用壽命；這僅為經驗值，並不具備必須履行的約束力。這些數值並不會構成保固時效期限的延長或對其造成任何形式的影響。


## Connector Drawings



### X1

- 2)  
1 — TX+  
2 — RX+  
3 — TX-  
4 — RX-

- 1) 視圖沿插接方向  
2) 插口, 4 針 / 功能  
3) 編碼 D



### X2

- 2)  
1 — n.c.  
2 — VDC  
3 — GND  
4 — n.c.  
5 — n.c.

- 1) 視圖沿插接方向  
2) 插頭, 5 針 / 功能