theLeda D U AL

Item no.: 1020903



LED-Leuchten LED-Leuchten mit Bewegungsmelder

Description

- Stylish LED light 8.5 W with motion detector (PIR)
- Light emission at top (up-light)
- High-quality housing made from anodised extruded-aluminium profiles
- Suitable for outdoor use
- Automatic lighting control based on presence and brightness
- 180° detection angle at 10 m range
- Teach-in, test, twilight switch, dimmable orientation light and selfcalculating night interruption functions can be adjusted via theSenda B and the theSenda Plug app
- High IP 55 protection rating for outdoor installation
- Easy installation with socket
- Wireless connectivity
- Exceptionally efficient thanks to high light output
- Long-lasting LEDs: service life of 50,000 hours
- Manual control via an interrupter switch (PERM ON 6 h)
- Product design by ID AID



Technical data

	theLeda D U AL	
Operating voltage	230 V AC	
Frequency	50 – 60 Hz	
Stand-by consumption	~0.5 W	
Colour	Aluminium (similiar RAL 9010)	
Installation type	Wall installation	
LED output (lighting current)	760 lm	
Colour temperature	3000 K, warmwhite	
Colour rendering index	< 80	
Service life	L80/B10/50.000 h	


	theLeda D U AL	
Setting range brightness	2 - 800 lx	
Detection angle	180°	
Light switch-off delay	10 s-20 min	
Remote controlled	✓	
Ambient temperature	-25°C 45°C	
Protection class	II	
Type of protection	IP 55	

theLeda D U AL

Item no.: 1020903




Connection example



Detection range for planning applications at a temperature of 21 °C

Mounting height (A)	Diagonally (t)	Head on to (R)
2.2 m	10 m	4 m





theLeda D U AL


Item no.: 1020903



Scale drawings







Accessories

theSenda P Item no.: 9070910







theSenda B Item no.: 9070985

